

URJETA ELECTRICALS

POLYCAB

IDEAS. CONNECTED.

L.P. : 20.03.2025

PRICE LIST

FLEXIBLE WIRES

w.e.f. : 20.03.2025

Polycab FR PVC Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Bright Annealed Copper Conductor for Voltage Grade 1100 Volts Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Flexible Cables for Voltage Grade 1100 Volts conforming to IS: 694:2010 (Price in Rs./100m)							
Nominal Area of Conductor (sq mm)	Single Core	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	1450	3695	5070	6480	5	8320	9935
0.75	2035	4950	6870	8825	5	11800	14200
1	2590	6285	8750	11300	5	15150	18250
1.5	3730	8550	12275	15900	5	20700	25200
2.5	6135	14100	19400	26200	4	33600	40700
4	9420	20700	29800	39600		53300	63900
6	14100	30500	43900	58300		78600	94300
10	24700	52100	76600	101100		135500	-
16	38500	82300	120300	158900		208100	-
25	60500	137800	200500	261900		379700	-
35	84800	191900	278600	366200		520400	-
50	120900	272300	396900	524100		753400	-
70	170800	386900	550500	727700		1030200	-
95	226400	-	-	-		-	-
120	291900	-	-	-		-	-
150	365400	-	-	-		-	-
185	456800	-	-	-		-	-
240	596300	-	-	-		-	-
300	746000	-	-	-		-	-
400	994000	-	-	-			
500	1243600	-	-	-			
630	1603900	-	-	-			

POLYCAB 1100 V. FLEXIBLE MULTICORE CABLES with annealed bare copper FRLS insulated & sheathed as per : 694-1990

HSN : 85446090

(Rate in Rupees per 100 meter)

SQ. MM.	SIZE	7 CORE	8 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.50	16/0.20	11200	13100	16300	19100	21900	25000	28900	36500
0.75	24/0.20	15800	18500	23200	27000	31700	35700	42200	52700
1.00	32/0.20	20600	23700	29400	35000	40700	46300	54400	68200
1.50	30/0.25	28400	32400	41300	48600	57500	66300	77000	98600
2.50	50/0.25	46700	54900	67400	81000	94100	107500	124500	161300
4.00	56/.3	77000	-	-	-	-	-	-	-

PLUS GST 18% EXTRA
P.T.O.

Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Single Core (Rate/100m)	FRLS FLEXIBLE CABLES (Rate/100m)				
		Two Core	Three Core	Four Core	Five Core	Six Core
0.5	1485	3930	5295	6715	8320	9935
0.75	2085	5240	7145	9100	11800	14200
1	2625	6565	9040	11600	15150	18250
1.5	3760	8890	12650	16200	20700	25200
2.5	6230	14600	19900	26800	33600	40700
4	9480	21300	30500	40300	53300	63900
6	14300	31300	44700	59000	78600	94300
10	25300	53000	77700	102800	135500	-
16	39100	84500	123100	161900	208100	-
25	61300	140600	204500	267400	379700	-
35	85700	195800	284100	374000	520400	-
50	121900	278000	404700	534200	753400	-
70	172700	394500	561300	742400	1030200	-
95	228900	-	795700	1049700	-	-
120	294400	-	1010300	1333400	-	-
150	369100	-	1263000	1667000	-	-
185	460900	-	1555300	2055800	-	-
240	602100	-	2007700	2657600	-	-
300	753500	-	2505400	3317600	-	-

POLYCAB 1100 V. FLEXIBLE MULTICORE CABLES with annealed bare copper FRLS insulated & sheathed as per is : 694-1990

(Rate in Rupees per 100 meter)

SQ. MM.	SIZE	7 CORE	8 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.50	16/0.20	11200	13100	16300	19100	21900	25000	28900	36500
0.75	24/0.20	15800	18500	23200	27000	31700	35700	42200	52700
1.00	32/0.20	20600	23700	29400	35000	40700	46300	54400	68200
1.50	30/0.25	28400	32400	41300	48600	57500	66300	77000	98600
2.50	50/0.25	46700	54900	67400	81000	94100	107500	124500	161300
4.00	56/1.3	77000	-	-	-	-	-	-	-

SOLAR WIRES/CABLES

Flexible Bare copper Conductor Single Core Multistand, Cross Linked, Zero Halogen Low Smoke Insulation and Cross Linked Low Smoke Sheathing, Heat Resistance and UV Resistant Solar Cables

(Rate per 100m. - Rs.)

HSN : 85446090

SIZE IN Sq.mm.	TINNED COPPER RATE RS.	EN 50618 RATE RS.
4	10900	11525
6	16050	16800

WELDING CABLES

Polycab Flexible Copper Conductor Elastomer Insulated welding Cable EPE 1100 Volts as per IS 9968 (Rate per 100 mtr)

CONDUCTOR ARE (SQ.MM.)	CURRENT CARRING CAPACITY	RATE PER 100 MTR. (RS.)
16	120	47300
25	160	73800
35	230	102100
50	400	145000
70	600	205000
95	700	270100
120	1100	345600

PLUS GST 18% EXTRA

URJETA ELECTRICALS

POLYCAB

IDEAS. CONNECTED.

L.P. : 20.03.2025

INDUSTRIAL (MULTISTAND) CABLES

w.e.f. : 20.03.2025

'Polycab' PVC Insulated fire retardant (FR), Flame resistant low smoke (FRLSH) - "Fire Brake" conforming to IS 694:1990 and EVA insulated zero halogen fire retardant (ZHFR) Single core unsheathed electrical wires with flexible bright annealed multistrand bare copper conductor for voltage grade upto 1100 volts.

HSN : 85446090

SIZE	RATE RS/200M.			RATE RS/300M.			STANDARD PACKING	
Sq.MM.	FRLF	FRLSH	FRZH	FRLF	FRLSH	FRZH	200M	300M
0.75	-	-	-	5980	6165	6495	-	10
1	-	-	-	7845	8075	8415	-	8
1.5	-	-	-	11540	11885	12400	-	6
2.5	-	-	-	18715	19290	20140	-	4
4	19250	19830	20705	-	-	-	4	-
6	28780	29650	30955	-	-	-	3	-
10	50425	51905	54165	-	-	-	1	-
16	-	-	-	-	-	-	1	-

'Polycab' Annealed Bare Copper Conductor PVC Insulated, TINED COPPER BRAIDED (SCREENED) PVC Sheathed Flexible Cable, 1100 Volts.

HSN : 85446020

Rate per 100 m.

UN-ARMoured								
CORES	16/0.2 MM 0.5 Sq.mm.	24/0.2 MM 0.75 Sq.mm	32/02 MM 1.00 Sq.mm	48/0.2 MM 1.5 Sq.mm.	80/0.2 MM 2.5 Sq.mm	4.0 Sq.mm	84/0.3 6 Sq.mm	7.36 Sq.mm.
2	11300	13900	15700	19000	28600	42600	55200	-
3	13200	17300	21100	26200	38300	60300	84400	-
4	16300	21100	25800	32700	48300	73600	102600	-
5	20600	25300	29600	38900	64900	-	-	-
6	21800	29600	33700	45600	72800	-	-	-
7	23500	33000	38300	50500	82300	-	-	-
8	27300	39200	43500	58200	85900	-	-	-
10	34700	43300	57900	73000	96100	-	-	-
12	40000	48900	62100	82300	112400	-	-	-
14	43300	57900	72800	98600	135000	-	-	-
16	46400	67500	81800	108900	159000	-	-	-
19	55200	79900	96500	135000	205300	-	-	-
24	66600	89200	121100	165500	257400	-	-	-
27	-	-	-	-	-	-	-	-
37	-	-	-	-	-	-	-	-

**PLUS GST 18% EXTRA
P.T.O.**

POLYCAB BUILDING MANAGEMENT SYSTEM CABLE (BMS)

Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Maylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Price in Rs./100m)

Core	0.5 Sq.mm.	0.75 Sq.mm	1.0 Sq.mm	1.5 Sq.mm	2.5 Sq.mm
2	6185	7920	9500	12400	19400
3	7670	10450	12600	17000	26800
4	9525	12650	16150	22600	33800
5	11700	15600	19000	26100	42700
6	13600	17800	22300	31900	51100
7	14700	20900	25900	35400	60500
8	16800	22600	28800	40100	67600
10	19900	27900	35400	49000	82600
12	23500	33200	42400	58800	101400
14	27300	38300	48300	66800	-
16	30900	43000	54300	77000	-
19	35400	51100	64300	89500	-
24	43900	62800	79500	114400	-

POLYCAB UNINYVIN CABLES

Multistand Annealed Tinned Copper Conductor 105° C PVC Insulation
with Nylon Braiding with Lacquer Coating Uninyvin Cables

Cable Size	Nom. Conductor Area (Sq.mm.)	Price in Rs./Mtr.
22	0.347	29.80
20	0.556	38.20
18	0.996	56.40
16	1.17	67.10
14	2.05	103.00
12	3.22	148.00
10	5.33	212.00
8	8.75	329.00
6	13.30	487.00
4	21.50	771.00
2	33.30	1179.00
1	40.70	1427.00
0	53.00	1854.00
00	68.30	2360.00
000	84.20	2924.00
0000	109	3761.00

Terms & conditions

- This cancels all our previous price list.
- Rates are Subject to change without prior Notice.

PLUS GST 18% EXTRA
P.T.O.

URJETA ELECTRICALS

POLYCAB

IDEAS. CONNECTED.

COMMUNICATION AND SUBMERSIBLE CABLES

W.e.f. : 20.03.2025

CO-AXIAL CABLES

Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded and PVC Black Jacket.

Type	Rate Per 100 Mtr.	Rate Per 305 Mtr.	Rate Per 1000 Mtr.
	Unarmoured		Armoured
RG - 59	2440	7460	-
RG - 6	3065	9400	101210
RG - 11	6995	21425	157900
RG - 06 CCS	1985	6045	-
RG - 11 CCS	4005	12205	-
RG - 6	-	-	-

LAN CABLES

Polycab UTP-4 pair Cat-5 Lan Cables

HSN : 85444992

Type	Rate per COIL OF 305 MTRS (RS.) Unarmoured	Rate per COIL OF 1000 MTRS (RS.) Armoured
CAT - 5E	12725	-
CAT - 6	-	-
CAT - 6 UTP (Without Separator)	13380	-
CAT - 6 UTP (With Separator)	13760	117920

CCTV CABLES

HSN : 85442010

GST 18% extra

CCTV CABLES	Rate / 90 meters
CCTV Cables 3+1	4015
CCTV Cables 4+1	4365

SPEAKER WIRES (Oxygen Free)

HSN : 85446090

(Rate in Rupees per 90 meter)

SIZE 23/36	SIZE 40/36	SIZE 70/36
SISSPK 1013	SISPK1012	SISSPK1011
2025	3105	4215
SIZE 23/38	SIZE 40/38	SIZE 70/38
SISSPK 1004	SISPK1005	SISSPK1006
1375	2280	3090

TELEPHONE CABLES

Polycab **Un-Armoured** High Conductivity Solid Annealed Bare Copper Telephone Cable with High Density Polyethylene Insulation, Paired, Polyester Taped and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming to ITD S/SW 113 C and Polycab Specifications

HSN : 85444992

RATE PER 100/90 MTRS COIL

No. Of Pairs	90 meters		100 meters	
	0.4mm	0.5 mm	0.4mm	0.5 mm
01 PAIR	725	1020	815	1140
02 PAIR	1280	1815	1420	2015
03 PAIR	1890	2685	2095	2985
04 PAIR	2420	3550	2680	3940
05 PAIR	2975	4405	3290	4885
10 PAIR	-	8555	-	9500
20 PAIR	-	16510	-	18390
50 PAIR	-	-	-	47690
100 PAIR	-	-	-	93335

POLYCAB PVC insulated and pvc sheathed cable with plain copper conductor having three core flat for SUBMERSIBLE MOTORS

HSN : 85446090

(Rate in Rupees per 100 meter)

SQ. MM.	Size in General	RATE PER 100 MTR (Rs.)
1.50	22/.3	10110
2.50	36/.3	15690
4.00	56/.3	23465
6.00	84/.3	34400
10.00	80/.4	59790
16.00	126/.4	92850
25.00	196/.4	145160
35.00	608/.5	201140
50.00	396/.4	-
70.00	354/.5	-